


### Key Features



- 15" Intel Broadwell Fanless Stainless Panel PC
- IP66 full sealed with Anti-corrosion enclosure
- 15" LCD with full flat Resistive touch
- IP67 M12 metal connectors
- Special inspection of 100% waterproof guarantee
- CE, FCC, VCCI Class B certified
- Wide Temp. -20~55°C operation capability
- Customized PCAP touch with IP69K true tested
- Customized IP67 solution
- Screen touch lock function



### Outline Drawing



### Main System

<b>CPU</b>	FCBGA1168 5th generation Intel® Core i7/i5 processor (15W max.)
<b>Chipset</b>	SoC
<b>VGA</b>	Intel® integrated HD Graphics 5500 by CPU
<b>Memory</b>	Two 1600 MHz DDR3L SODIMM socket support dual Channel, non-ECC, up to 16GB

### LCD Panel

<b>Size</b>	15" 4:3
<b>Resolution</b>	1024 x 768 (XGA)
<b>Color numbers</b>	16.7M colors (RGB 6bit + HIFRC)
<b>Viewing angle</b>	160 (H) / 160 (V)
<b>Contrast</b>	600:1
<b>Brightness</b>	300 nits

### Touch Panel

<b>Type</b>	Full Flat Resistive touch, 5-wire
<b>Light transmission</b>	80±5%
<b>Hardness</b>	4H
<b>Life time</b>	350,000hours

### Storage & Expansion

<b>SSD</b>	128GB 2.5" SATA SSD 3MG2-P x 1
<b>Expansion slot</b>	Mini PCIe x 2

### I/O & Power & Control Keys

<b>USB</b>	1 x M12 8pin for USB 1/2 1 x M12 8pin for USB 3/4
<b>COM</b>	1 x M12 8pin for COM 1/RS-232 1 x M12 8pin for COM 2/RS-232
<b>LAN</b>	1 x M12 8pin for LAN 1
<b>Power input</b>	1 x M12 5pin DC power connector, DC7V~32V
<b>Power adaptor</b>	AC 90 ~ 264V / 47 ~ 63 Hz / DC output 12V IP67, 60W
<b>Power consumption</b>	53.3 W ( MAX. Loading without adapter )
<b>Control keys</b>	Rear bottom: Power on/off

### Mechanical & Environmental


<b>Housing</b>	Stainless steel (SUS304), chassis type
<b>IP rating</b>	IP66 whole set (include the I/O connectors & control keys)
<b>Cooling</b>	Fanless
<b>Dimension</b>	395 x 309.5 x 58 mm (W x H x D, not include I/O connectors)
<b>Weight (net)</b>	8.4 Kg (net)
<b>Temperature</b>	Operating -- -20°C~55°C (air flow cooling)
<b>Humidity</b>	Storage -- -20°C~60°C Operating & storage -- 10%~90%, non-condensing
<b>Regulatory</b>	FCC, CE (EMC), VCCI Class B

### Options

Wireless or Wireless + BT kit (2 ant)
M12 to 1x COM cable (cable length is 2 meters)
M12 to 1x USB cable (1 USB Port) (cable length is 2 meters)
M12 to 2x USB cable (2 USB Port) (cable length is 2 meters)
M12 to 1x LAN cable (cable length is 2 meters)
Wall mount / table mount bracket

### Customization

1000 nits high brightness LCD
Sunlight readable optical bonding
Anti UV and 7H coating
LCD Auto dimming
LCD Super dimming (Low brightness)
Robust Antenna
Full flat PCT touch screen IP69K
USB 3.0
5W/2W speaker
2 External LAN (USB x2, LAN x2, COM x1)
Intel Core i7-5500U turbo mode disable
Second HD
IP67



- 1 Giga LAN
- 2 USB 1/2
- 3 USB 3/4
- 4 COM x 2
- 5 DC-in
- 6 Power on/off



Wall Mount

### Ordering Information

WTP-9C66-15W (i5)	15" FANLESS	Core i5-5200U / 4G RAM / 128 SSD / Full flat R-Touch
-------------------	-------------	--