


Key Features



- 19" Intel Broadwell Fanless Stainless Panel PC
- IP66 full sealed with Anti-corrosion enclosure
- 19" LCD with full flat Resistive touch
- IP67 M12 metal connectors
- Special inspection of 100% waterproof guarantee
- CE, FCC, VCCI Class B certified
- Wide Temp. -20~55°C operation capability
- Customized PCAP touch with IP69K true tested
- Customized IP67 solution
- Screen touch lock function



Outline Drawing



Main System

CPU	FCBGA1168 5th generation Intel® Core i7/i5 processor (15W max.)
Chipset	SoC
VGA	Intel® integrated HD Graphics 5500 by CPU
Memory	Two 1600 MHz DDR3L SODIMM socket support dual Channel, non-ECC, up to 16GB

LCD Panel

Size	19" 4:3
Resolution	1280 x 1024 (SXGA)
Color numbers	16.7M colors (RGB 6bit + HIFRC)
Viewing angle	170 (H) / 160 (V)
Contrast	1000:1
Brightness	350 nits

Touch Panel

Type	Full Flat Resistive touch, 5-wire
Light transmission	80±5%
Hardness	4H
Life time	490,000hours

Storage & Expansion

SSD	128GB 2.5" SATA SSD 3MG2-P x 1
Expansion slot	Mini PCIe x 2

I/O & Power & Control Keys

USB	1 x M12 8pin for USB 1/2 1 x M12 8pin for USB 3/4
COM	1 x M12 8pin for COM 1/RS-232 1 x M12 8pin for COM 2/RS-232
LAN	1 x M12 8pin for LAN 1
Power input	1 x M12 5pin DC power connector, DC7V~32V
Power adaptor	AC 90 ~ 264V / 47 ~ 63 Hz / DC output 12V IP67, 60W
Power consumption	67.5 W (MAX. Loading without adapter)
Control keys	Rear bottom: Power on/off

Mechanical & Environmental


Housing	Stainless steel (SUS304), chassis type
IP rating	IP66 whole set (include the I/O connectors & control keys)
Cooling	Fanless
Dimension	458 x 386 x 64 mm (W x H x D, not include I/O connectors)
Weight (net)	11.5 Kg (net)
Temperature	Operating -- -20°C~55°C (air flow cooling) Storage -- -20°C~60°C
Humidity	Operating & storage -- 10%~90%, non-condensing
Regulatory	FCC, CE (EMC), VCCI Class B

Options

- Wireless or Wireless + BT kit (2 ant)
- M12 to 1x COM cable (cable length is 2 meters)
- M12 to 1x USB cable (1 USB Port) (cable length is 2 meters)
- M12 to 2x USB cable (2 USB Port) (cable length is 2 meters)
- M12 to 1x LAN cable (cable length is 2 meters)
- Wall mount / table mount bracket

Customization

- 1000 nits high brightness LCD
- Sunlight readable optical bonding
- Anti UV and 7H coating
- LCD Auto dimming
- LCD Super dimming (Low brightness)
- Robust Antenna
- Full flat PCT touch screen IP69K
- USB 3.0
- 5W / 2W speaker
- 2 External LAN (USB x2, LAN x2, COM x1)
- Intel Core i7-5500U turbo mode disable
- Second HD
- IP67



- 1 Giga LAN
- 2 USB 1/2
- 3 USB 3/4
- 4 COM x 2
- 5 DC-in
- 6 Power on/off



Ordering Information

WTP-9C66-19 (i5) 19" FANLESS Core i5-5200U / 4G RAM / 128 SSD / Full flat R-Touch