

WLP-7D20 Series

User's Manual

Version V1.0

Copyright © 2016, ALL RIGHTS RESERVED.

All other brand names are registered trademarks of their
respective owner

Copyright Notice
Copyright © 2016
All Rights Reserved.
Printed in Taiwan.

The information contained in this document is subject to change without any notices.

Acknowledgments

Greeting & Setup

Thank you for purchasing the WLP-7D20 Panel PC. We wish that this unit will be durable and reliable in providing your needs. Please follow the instructions below to ensure the unit continues to have high performance

Unpacking

After opening the carton, there will be a unit with an accessory box. Examine the contents to see if there are damages to the unit and if all accessories are present.

Setting up

Please read this manual carefully and remember to keep this manual for future reference.

Safety Instructions & Cleaning

The unit has undergone various tests in order to comply with safety standards. Inappropriate use may be dangerous. Please remember to follow the instructions below to insure your safety during the installation and operating process.

Transporting & Placement of unit

-
1. When moving the unit on a cart; be very cautious. Quick stops, excessive forces and uneven surfaces may cause the cart to overturn thus risking the unit to fall to the ground.
 2. If the Monitor display unit does fall to the ground, immediately turn the power off and disconnect cords. Then contact a service technician for repairs. Continual use of the unit may result cause a fire or electric shock. Also, do not repair the unit on your own.
 3. Having two or more people transporting the display unit is recommended. In addition, when installing the open frame by suspending it also requires two or more people.
 4. Before suspending the unit, make sure the material used for suspension is sturdy and stable. If not properly suspended, the display unit may fall and cause serious injury to people standing nearby as well as to the unit itself.
 5. If you wish to mount the display unit, remember to use only the mounting hardware recommended by the manufacturer.

Electrical and Power Source Related

1. This Monitor display unit must operate on a power source as shown on the specification label. If you are not sure what type of power supply used in the area, consult your dealer or local power supplier.
2. The power cords must not be damaged. Applied pressure, added heat, and tugging may damage the power cord.
3. The power cord must be routed properly when setup takes place. We advise that this aspect measure is to prevent people from stepping on the cords or while the unit is suspended to prevent flying objects from getting tangled with

the unit.

4. Do not overload the AC outlets or extension cords. Electrical shocks or fires may occur from overloading.
5. Do not touch the power source during a thunderstorm.
6. If your hands are wet, do not touch the plug.
7. Use your thumb and index finger, grip firmly on the power cord to disconnect from the electrical socket. By pulling the power cord, may result in damaging it.
8. If the unit is not going to be in use for an extended period of time, remember to disconnect the unit.
9. Connect the unit to a power source with the same numerical value as spec. label shown. Please use only the power cord provided by the dealer to ensure safety and EMC compliance.

Various Factors of Environment

1. Do not insert objects into the openings.
2. Do not have liquids seep into the internal areas of the Monitor display unit.
3. Having liquids seep in or inserting objects into the unit may result in electric shocks from taking and/or short circuiting the internal parts.
4. Do not place the Monitor display unit in the presence of high moisture areas.
5. Do not install the Monitor display unit in a wet environment.
6. Do not place near unit near heat generating sources.
7. Do not place the unit in a location where it will come in contact with fumes or steam.
8. Remember to keep the Monitor display unit away from the presence of dust.

-
9. If water has flow in or seep in, immediately disconnect the open frame unit. Then contact a service technician for repairs.

Ventilation Spacing

1. Do not cover or block the openings on the top and back sides of the display unit. Inadequate ventilation may cause overheating thus reducing the lifespan of the unit.
2. Unless proper ventilation is present, do not place unit in an enclosed area; such as a built-in shelf. Keep a minimum distance of 10 cm between the display unit and wall.

Cleaning the unit

1. Remember to turn off the power source and to unplug the cord from the outlet before cleaning the unit.
2. Carefully dismount the unit or bring the unit down from suspension to clean.
3. Use only a dry soft cloth or clean room wiper when cleaning the LCD panel or touch screen surface. Use a soft cloth moistened with mild detergent to clean the display housing.
4. Remember to avoid having liquids seep into the internal components.

Servicing, Repairing, Maintenance & Safety Checks

1. If the unit is not functioning properly, observe the performance level of the display closely to determine what type of servicing is needed.
2. Do not attempt to repair the Monitor display unit on your own. Disassembling the cover exposes users' to high voltages and other dangerous conditions. Notify and request a qualified service technician for servicing the unit.

-
3. If any of the following situations occur turn the power source off and unplug the unit. Then contact a qualified service technician
 - i. A liquid was spilled on the unit or objects have fallen into the unit.
 - ii. The unit is soaked with liquids.
 - iii. The unit is dropped or damaged.
 - iv. If smoke or strange odor is flowing out of the open frame unit.
 - v. If the power cord or plug is damaged.
 - vi. When the functions of the unit are dysfunctional.
 4. When part replacement is needed. Make sure service technician uses replacement parts specified by the manufacturer, or those with the same characteristics and performance as the original parts. If unauthorized parts are used it may result in starting a fire, electrical shock and/or other dangers.

Battery Installation

Follow below instructions and notice the caution for replacing and disposing of the RTC Lithium battery CR2032 for safety consideration.

CAUTION:

There is danger of explosion, if battery is incorrectly replaced. Replace only with the same or equivalent type recommended by the manufacturer. Dispose of used batteries according to the manufacturer's instruction.

The specification is subject to change without notice.

Version Change History

Date	Version	Description	Remark
2016/11/07	V1.0	First release	Eddie

Table of Contents

How to Use This Manual.....	IX
System Overview.....	1
System View.....	7
I/O connectors	9
VESA mount installation.....	10
Panel mount installation	10
Unpacking	13
Getting Started	15
Setting up the System	15
Installing System Software.....	15
Installing the Drivers	16
Appendix.....	33
A. Jumper settings and Connectors	33
B. Wake UP on LAN Function.....	68

How to Use This Manual

This manual is written for the system integrator, PC technician and knowledgeable PC end user. It describes how to configure your WLP-7D20 Panel PC to meet various operating requirements. The user's manual is divided into three chapters, with each chapter addressing a basic concept and operation of the server board.

Chapter 1: System Overview - presents what you have inside the box and gives you an overview of the product specifications and basic system architecture for the WLP-7D20 Panel PC.

Chapter 2: System Installation - describes how to set up the system.

Chapter 3: BIOS Setup Information - specifies the meaning of each setup parameter, how to get advanced BIOS performance and update to a new BIOS. Additionally, the POST checkpoint list will give you a guide for troubleshooting.

The contents of this manual are subject to change without prior notice. These changes will be incorporated in new editions of this manual.

System Overview

System Specification

CPU	Intel® Core-I i5-5200U 2.2 GHz dual-core processor	
Chipset	Intel® HD Graphics 5500	
Audio	Realtek ALC262 Audio Codec, 2+2 watts power amplifier	
LAN	Intel® I210-AT Gigabit Ethernet x 2	
Memory	Dual Channel, two DDR3L SO-DIMM socket support up to 8GB DDR3L-1333MHz	
I/O	EC	
Serial ATA	<i>SATA 3, 600 MB/s transfer rate x 2</i>	
Serial port	External	RS232/RS422/RS485 x 1(Set by BIOS, RS485 auto flow), RS232 x 1
	Internal	RS232 x 1
		RS232 (Jumper 5V, 12V) x1
USB	External	USB 3.0 x 4 (Type A)
	Internal	USB 2.0(5V) pin head x 4, (total internal usb2.0x 7; pin head x 4: one for R/PCT touch, one for USB webcam control, two for pin head x 2; reserved USB x 3: two for miniPCIE and one for ISO_USB)
WDT	Generates system reset; 256 segments, 0, 1, 2...255 sec/min.	

BIOS f

Brand: AMI

Flash ROM size: 64Mb

Support RTC wakeup /Wake on LAN /Power on after power failure/PnP/ACPI/RTC

Display Panel

Size	15"	17"	19"
Brand	TIANMA	AUO	AUO
Model	TM150TDSG70	G170ETN01.0	G190EG01
Resolution (pixel)	SVGA (1024 x 768)	1280 (H) x 1024(V)	1,280 (H) x 1024 (V)
Number of Colors	16.2M	16.7M	16.7 M
View Angle (H/V)	160/160	170/160	170/160
Brightness (cd/m2)	300	350	350
Contrast Ratio	600:1	1000 : 1	1000 : 1
Interface	LVDS	LVDS	LVDS 6-bit
Supply Voltage (V)	3.3	3.3	3.3
Backlight	LED	LED	LED
life time<Hrs>	30000	30000	50000
Operating temp.	-20~70°C	0~50°C	0~80°C

Size	21"
Brand	AUO
Model	M215HTN01.1
Resolution (pixel)	SVGA (1920 x 1080)
Number of Colors	16.7 M
View Angle (H/V)	170/160
Brightness (cd/m2)	250
Contrast Ratio	100:1
Interface	LVDS 6 bits
Supply Voltage (V)	3.3
Backlight	CCFL
life time<Hrs>	30000
Operating temp.	0~50°C

Continuous displaying fixed pattern may induce image sticking. It's recommended to use screen saver or moving content periodically if fixed pattern is displayed on the screen.

Cautions:

Continuous displaying fixed pattern may induce image sticking. It's recommended to use screen saver or moving content periodically if fixed pattern is displayed on the screen.

Touch Screen: resistive or capacitive types

	ELO	HIGGSTEC
Type	5 wire Full Flat Res. touch	Projective Capacitive
Glove	Any type glove	No
Input Mode	Point: Finger or touch pen Drag: Finger	Finger P-Cap touch pen
Vandal	NA	NA
Interface	USB	USB
Light Transmission	80±5%	90±3%
Hardness	4H	7H
Glass thickness	2.5 mm	3.45 mm
Linearity	$X \leq 1\%$, $Y \leq 1\%$	$X \leq 1.0\%$, $Y \leq 1.0\%$
Resolution	4096x4096	25ppi
Lifetime	36 million activations	100 million activations

Touch Controller

EETI EXC7700 microcontroller with USB interface and specific for 4, 5, 8 wire touch screen.

Storage

HDD	2.5" SATA HDD drive bay x 1 (with anti-vibration mechanism)
SATA DOM	2 nd SATA connector pin7 with VCC_(+5V)

Expansion

Mini-PCIE	52 pin card-edge type compatible to PCI Express*Base specification 2.0 x 2
-----------	--

External I/O

USB	USB 2.0 x 3, USB 3.0 x 1 (internal USB 2.0 x 5 → one for Res. Touch or PCT, two for Mini PCI-e or USB 2.0, Three for Free)
COM	RS232/RS422/RS485 x 1(Set by BIOS, RS485 auto flow), RS232 x 2
LAN	RJ-45 x 2 (Gigabit Ethernet)
Audio	3.5mm phone jack connector * 2 (Line-out, and Mic-in)
DVI output	DVI-I x 1

Power

Power	DC-In connector x 1 (Jack with locker)
Switch	Reset key
LED indicator on	Green: power On/Off
Aluminum bezel	Red: HDD status
Power Input	DC12V~28V
Power Adapter	AC 90 ~ 264V / 47 ~ 63 Hz / DC output 12V

Mechanical & Environmental

Material construction	Front bezel is Aluminum or SECC, others are SECC enclosure
Aluminum bezel Color	Black / Silver
Front Panel Protection	Res. Touch IP66 / P-CAP touch IP69K
ID design	Panel mount (default)
Operation Temperature	12V DC Input 0~50°C (IEC60068-2-56, air flow cooling) 12V DC Input 0~40°C (IEC60068-2-2, natural cooling) 32V DC Input 0~40°C (IEC60068-2-2, natural cooling)
Storage Temperature	-20~65°C
Operation Relative Humidity	10%~90%, non-condensing
Storage Relative Humidity	10%~90%, non-condensing
Mounting	Panel mount/VESA (75x75)


	Net Weight (Kg)	Gross Weight (Kg)
15"	5.5kg	8.5kg
17"	8.3kg	10.5kg
19"	9.2kg	12.4kg
21"	10kg	13.4kg

Shock/Vibration/Drop


	<i>Shock</i>	<i>Vibration</i>	<i>Drop</i>
<i>General</i>	<i>Operating:</i> <i>Pulse shape :</i> <i>Half-sine waveform</i> <i>Impact</i> <i>acceleration : 15g</i> <i>Pulse duration : 11</i> <i>ms</i> <i>Number of shocks :</i> <i>18 shocks (3 shock</i> <i>for each \pmaxis)</i> <i>Orientation : \pmX, \pmY</i> <i>and \pmZ axes</i>	<i>Operating:</i> <i>5 ~ 500Hz ,</i> <i>Acceleration : 1.0G</i> <i>Sweep time : 15</i> <i>minutes</i> <i>Number of cycle : 1</i> <i>cycle for each axis</i> <i>Vibration axes : X, Y</i> <i>and Z</i>	<i>3 Feet height free</i> <i>drop still survive,</i> <i>(test surface:</i> <i>concrete, with</i> <i>packing)</i> <i>6 surfaces</i>

System View


WLP-7D20-15 Outline Drawing (Panel Mount)




WLP-7D20-17 Outline Drawing (Panel Mount)



WLP-7D20-19 Outline Drawing (Panel Mount)



WLP-7D20-21 Outline Drawing (Panel Mount)



I/O connectors




Note: Share the same place with DVI output, DVI and VGA not simultaneously

VESA mount installation

Please use the supplied 4 x M4-L10 screws for VESA mounting. And as below VESA mounting holder is just a diagrammatic drawing. You can choose any standard VESA 75x75 mm mounting holder to mount our machine.

For use only with UL listed Wall Mount Bracket with minimum weight/load bearing capacity 10 Kg




Panel mount installation


1. The Panel PC can be panel mounted and comes with brackets and screws for this purpose. The required cutout for panel mounting and maximum panel thickness is shown below.

	A	B	C
WLP-7D20-15	365	298	10
WLP-7D20-17	398	325	14
WLP-7D20-19	460	360	14
WLP-7D20-21	549	340	13

Unit: mm





STEP 1




Panel Mount

Put Panel PC on the fixture (Wall, Panel.....) from the front, with the sides of the front bezel shown on the outside.

STEP2



Use provided mounting kits to fix the Panel PC and the customer's fixture



Unpacking

After unpacking the shipping carton, you should find these standard items:

- The WLP-7D20 Panel PC series
- Accessory box including the followings:
 - AC-DC adapter x 1
 - AC power cord x 1
 - Screws (M3x0.5PxL6) x 8

- Screws (M4x0.7PxL44) x 8
- CD-ROM for drivers, utility, user manual(in PDF format)

Inspect all the items. If any item is damaged or missing, notify your dealer immediately.

Getting Started

This chapter tells you how to set up the system.

Setting up the System

The following is a summary of the steps in setting up the system for use.

CAUTION: Make sure that power to the system and each of the devices to be connected is switched OFF before plugging in the connectors.

1. Make any required external connections such as the keyboard, and mouse.
2. Plug the appropriate end of the power cord into the power connector of the system. Then plug the other end of the power cord to an electrical outlet.
3. Press the power switch of the system to turn on the system's power.
4. If necessary, run the BIOS SETUP program to configure the system (see Chapter 3).
5. Install the software drivers if necessary.

Installing System Software

Recent releases of operating systems from major vendors include setup programs, which load automatically and guide you through hard disk preparation and operating system installation. The guidelines below will help you determine the steps necessary to install your operating system on the Panel PC hard drive.

NOTE: Some distributors and system integrators may have already pre-installed system software prior to shipment of

your Panel PC.

Installing software requires an installed HDD. Software can be loaded in the WLP-7D20 Panel PC using any of below methods:

Method 1: Use the Ethernet

You can use the Ethernet port to download software from the net to the HDD that has been pre-installed in WLP-7D20 Panel PC

Method 2: Use the COM Port

By connecting another PC to the WLP-7D20 Panel PC with an appropriate cable, you can use transmission software to transmit Operation System Software to the HDD that has been pre-installed in the WLP-7D20 Panel PC.

Method 3: Use a External CD-ROM

In order to boot up system from USB-CD/DVD drive, please connect USB-CD/DVD drive, turn on computer power, keep on pressing "F11" key, go into BIOS quick boot menu, select "USB-CD ROM", WAIT FOR 20 SECONDS, then press enter, system OS will boot up from USB-CD/DVD drive directly

Then you can use the external CD-ROM to transmit the software to the HDD that has been pre-installed in the WLP-7D20 Panel PC

Installing the Drivers

After installing your system software, you will be able to set up the LAN, VGA, Audio and USB functions. All drivers are stored in a CD disc, which can be found in your accessory pack.

The various drivers and utilities in the disc have their own text files that help users install the drivers and understand their functions.

Follow the sequence below to install the drivers:

Step 1 – Install Intel® INF Driver

Step 2 – Install Intel® VGA Driver

Step 3 – Install Intel® LAN Driver

Step 4 – Install Audio Driver

Step 5 – Install Touch Driver

Step 1 – Install Intel® INF Driver

1. Open file of **chipset**
2. Click on the **setup.exe**
3. Follow the instructions that the window shows
4. The system will help you install the driver automatically
5. Reboot system

Step 2 –Install Intel® VGA Driver

1. Open file of **VGA**
2. Select the OS folder your system is
3. Click on the **.exe** file located in the OS folder
4. Follow the instructions that the window shows
5. The system will help you install the driver automatically
6. Reboot system

Step 3 – Install Intel® LAN Driver

1. Open file of **LAN**
2. Click on the **setup.exe**
3. Follow the instructions that the window shows
4. The system will help you install the driver automatically
5. Reboot system

Step 4 – Install Audio Driver

1. Open file of **LAN**
2. Click on the **setup.exe**
3. Follow the instructions that the window shows
4. The system will help you install the driver automatically
5. Reboot system


Step 5 – Install Touch Driver

1. Open file of **touch**
2. Click on the **setup.exe**
3. Follow the instructions that the window shows
4. The system will help you install the driver automatically
5. Reboot system

Note:

eGalax Touch driver supports both resistive and capacitive touch screens, user can find 2 touch icons shown in utility, please set up touch screen by selecting the correlative one.

(USB controller: resistive touch screen, USB controller: capacitive touch screen)



BIOS Setup

BIOS Introduction

The AMI BIOS (Basic Input / Output System) installed in your computer system's ROM supports Intel processors. The BIOS provides critical low-level support for a standard device such as disk drives, serial ports and parallel ports. It also adds virus and password protection as well as special support for detailed fine-tuning of the chipset controlling the entire system.

BIOS Setup

The AMI BIOS provides a Setup utility program for specifying the system configurations and settings. The BIOS ROM of the system stores the Setup utility. When you turn on the computer, the AMI BIOS is immediately activated. Pressing the key immediately allows you to enter the Setup utility. If you are a little bit late pressing the key, POST (Power On Self Test) will continue with its test routines, thus preventing you from invoking the Setup. If you still wish to enter Setup, restart the system by pressing the "Reset" button or simultaneously pressing the <Ctrl>, <Alt> and <Delete> keys. You can also restart by turning the system Off and back On again. The following message will appear on the screen:


Press to Enter Setup

In general, you press the arrow keys to highlight items, <Enter>

to select, the <PgUp> and <PgDn> keys to change entries, <F1> for help and <Esc> to quit.

When you enter the Setup utility, the Main Menu screen will appear on the screen. The Main Menu allows you to select from various setup functions and exit choices.

Main



This section provides information on the BIOS information, and Battery information


System Date

Set the system date. Use the <Tab> key to switch between data elements.

System Time

Set the system time. Use the <Tab> key to switch between time elements.

Advanced



Trusted Computing Configuration

Enables or disables BIOS support for security device. O.S. will not show Security Device. TCG EFI protocol and INT1A interface will not be available.

ACPI Settings

Enable Hibernation

Enables or Disables System ability to Hibernate (OS/S4 Sleep State). This option may be not effective with some OS.

ACPI Sleep State

Select the highest ACPI sleep state the system will enter when the SISPEND button is pressed.

F81216 Super IO Configuration

Serial Port 1 Configuration

Serial Port

Enable or Disable Serial Port (COM).

Function

RS232,RS422,RS485

Change Settings

Select an optimal settings for super IO Device.

Change Settings

Select an optimal settings for Super IO Device.
Set Parameters of Serial Port 1.

Serial Port 2 Configuration

Serial Port

Enable or Disable Serial Port (COM).

Change Settings

Select an optimal settings for super IO Device.

Serial Port 3 Configuration

Serial Port

Enable or Disable Serial Port (COM).

Change Settings

Select an optimal settings for super IO Device.

Serial Port 4 Configuration

Serial Port

Enable or Disable Serial Port (COM).

Serial Port 5 Configuration

Serial Port

Enable or Disable Serial Port (COM).

Serial Port 6 Configuration

Serial Port

Enable or Disable Serial Port (COM).

Change Settings

Select an optimal settings for super IO Device.

Intel(R) Smart Connect Technology

ISCT Support

Enable/Disable Intel Smart Connect

S5 RTC Wake Settings

Wake system From S5

Enable or disable System wake on alarm event. Select

FixedTime, System will wake on the hr::min::sec specified.

Select DynamicTime , System will wake on the current time + Increase minute(s).

CPU Configuration

Socket 0 CPU Information

Socket specific CPU Information.

IDE Configuration

Serial-ATA (SATA)

Enable / disable Serial ATA.

SATA Test Mode

Test Mode enable / disable.

SATA Speed Support

SATA Speed Support Gen1 or Gen2.

SATA ODD Port

SATA ODD is Port0 or Port1.

SATA Mode

Select IDE / AHCI

Serial-ATA Port 0

Enable / Disable Serial ATA Port 0.

SATA Port0 HotPlug

Enable / Disable SATA Port0 HotPlug.

Serial-ATA Port 1

Enable / Disable Serial ATA Port 1.

SATA Port0 HotPlug

Enable / Disable SATA Port1 HotPlug

Embedded Controller Configuration

Lock key click time

Number of seconds to press lock key to (un)active.

1~10 seconds mean press hold time.

Locked Status Hold Time

Number of minutes to keep lock status. 0 means lock always.

1~100 minutes mean lock hold time.

Power key

Enable / Disable power key.

Mute key

Enable / Disable Mute key.

Volume Up/Dn keys

Enable / Disable Vol+/Vol- key.

LCD Brightness Up/Dn keys

Enable / Disable LCD Brightness up/down key.

LCD Backlight On / Off key

Enable / Disable LCD Backlight key.

Lock key

Enable / Disable Lock key.

Webcam key

Enable / Disable webcam key.

Fn key

Enable/Disable Function key

Miscellaneous Configuration

PCI Express Dynamic Clock Gating

Enable / Disable PCIE Dynamic Clock Gating.

Show/hide hidden items

For debug only.

Show / hide hidden items.

Info Report Configuration

Post Report

Post Report Support Enabled / Disabled.

Info Error Message

Info Error Message Support Enabled / Disabled.

Summary Screen

Summary Screen Support Enabled / Disabled.

USB Configuration

USB Support

USB Support Parameters.

Legacy USB Support

Enables Legacy USB support. AUTO option disables legacy support if no USB devices are connected. DISABLE option will keep USB devices available only for EFI applications


XHCI Hand-off

Enable / Disable XHCI Controller Legacy support.

USB Mass Storage Driver Support

Enable/Disable USB Mass Storage Driver Support.

Chipset



North Bridge

Config Intel IGD Settings.

South Bridge

High Precision Timer

Enable or Disable the High Precision Event Timer.

Audio Controller

Control Detection of the Azalia device.

Disabled = Azalia will be unconditionally disabled.

Enable = Azalia will be unconditionally Enabled.

Auto = Azalia will be enabled if present disabled otherwise.

Restore AC Power Loss

Select AC power state when power is re-applied after a power failure.

Security

Aptio Setup Utility - Copyright (C) 2015 American Megatrends, Inc.					
Main Advanced Chipset Security Boot Save & Exit					
<p>Password Description</p> <p>If ONLY the Administrator's password is set, then this only limits access to Setup and is only asked for when entering Setup.</p> <p>If ONLY the User's password is set, then this is a power on password and must be entered to boot or enter Setup. In Setup the User will have Administrator rights.</p> <p>The password length must be in the following range:</p> <table><tr><td>Minimum length</td><td>3</td></tr><tr><td>Maximum length</td><td>20</td></tr></table> <p>Administrator Password</p> <p>User Password</p> <p>HDD Security Configuration:</p> <p>P0:TOSHIBA MQ01</p>	Minimum length	3	Maximum length	20	<p>Set Administrator Password</p> <hr/> <p>←+: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit</p>
Minimum length	3				
Maximum length	20				

Version 2.17.1246. Copyright (C) 2015 American Megatrends, Inc.

Administrator Password

Set Administrator Password.


User Password

Set user Password.

P0 : TOSHIBA MQ01

HDD Security Configuration for selected drive.

Boot



Setup Prompt Timeout

Number of seconds to wait for setup activation key. 65535(0xFFFF) means indefinite waiting.

Bootup Numlock State

Selects the keyboard NumLock state.

PXE Boot

PXE Network Boot Enable / Disable.

OS Selection

OS Selection.

Quiet Boot

Enable or disables Quiet Boot option.


Boot Option #1

Sets the system boot order.

Boot Option #2

Sets the system boot order.

Save & Exit



Save Changes and Exit

Exit system setup after saving the changes.

Discard Changes and Exit

Exit system setup without saving any changes.

Save Changes and Reset

Reset the system after saving the changes.

Discard Changes and Reset

Reset system setup without saving the changes.

Save Changes

Save the changes done so far to any of setup options.

Discard Changes

Discard the changes done so far to any of setup options.

Restore Defaults

Restore/load default values for all the setup options.

Save as User Defaults

Save the changes done so far as User Defaults.

Restore User Defaults

Restore the User Defaults to all the setup options.

Boot Override

To *override* the *boot* device.

Launch EFI Shell From filesystem device

Attempts to Launch EFI Shell application (Shell.efi) from one of the available filesystem devices.

Reset System with ME disable ModeMEUD000

ME will runs into the temporary disable mode, Ignore if ME Ignition FWMEUD001.


Appendix

A. Jumper settings and Connectors


This appendix gives the definitions and shows the positions of jumpers, headers and connectors. All of the configuration jumpers on WLP-7D20 series are in the proper position.

Note: Some of jumpers or connectors will be removed base on system configuration.

Jumper and Connector Definition Block




● JP1 – Touch Panel Type Selection




Description	Jumper Setting
3M type	1-2, 3-4 (default)
ELO type	5-6, 7-8

● JP2 – LVDS Power Selection




Description	Jumper Setting
+3.3VS(for 10"/12"/15")	5-6, 7-8
+5VS(for 17"/19")	1-2, 3-4 (default)

● JP3 – Backlight Type Selection




Description	Jumper Setting
Analog Inverter	1-2
PWM Inverter	2-3

● JP5 – Sensor Selection



Description	Jumper Setting
No Panel Sensor	1-2(default)
MB Sensor 25C	3-4(default)
MB auto sensor	5-6


● JP6 –Panel Resolution Selection



Jump on =0, Jump off =1


JP15 jumper setting				Panel Resolution	Color Depth
1-2	3-4	5-6	7-8		
0	0	0	0	800x600	6bit
0	0	0	1	1024x768	6bit
0	0	1	0	1024x768	8bit
0	0	1	1	1280x768	6bit
0	1	0	0	1280x800	6bit
0	1	0	1	1280x960	6bit
0	1	1	0	1280x1024	8bit
0	1	1	1	1366x768	6bit
1	0	0	0	1366x768	8bit
1	0	0	1	1440x900	8bit
1	0	1	0	1440x1050	8bit
1	0	1	1	1600x900	8bit
1	1	0	0	1680x1050	8bit
1	1	0	1	1600x1200	8bit
1	1	1	0	1920x1080	8bit
1	1	1	1	1920x1200	8bit

● JP7 –mSATA / mini-PCIE Selection




Description	Jumper Setting
<i>Mini-PCle</i>	<i>1-2 (default)</i>
mSATA	2-3

● JP8 – CMOS Clear




Description	Jumper Setting
<i>Normal Open</i>	<i>1-2 (default)</i>
CMOS Clear	2-3

● JP9 – SATA / SATADOM Selection



Description	Jumper Setting
<i>SATA</i>	<i>2-3(default)</i>
SATA DOM	1-2

● JP10 – COM4 Power Selection




Description	Jumper Setting
<i>+5VS</i>	<i>2-3(default)</i>
+12VS	1-2

● JP11 – Heater Test Selection




Description	Jumper Setting
<i>Normal</i>	<i>Open (default)</i>
Heater Test	1-2

● JP12 – PCT/RES Touch Selection



Description	Jumper Setting
<i>PCT Touch</i>	<i>1-2(default)</i>
RES Touch	2-3


● JP13 – Backlight Control Level Selection



Description	Jumper Setting
+3V	2-3
+3.3V	1-2
+5V	OPEN (default)


1.1 Connector Definition

● PJ1 /PJ2 – HDD Power Connector




Pin #	Signal Description
1	+12VS
2	GND
3	GND
4	+5VS

● PJ3 – Battery Connector




Pin #	Signal Description
1	BATT+
2	BATT+
3	BATT+
4	BATT_T
5	BATT_CLK
6	BATT_DAT
7	BATT_EN#
8	Ground
9	Ground
10	Ground

● PJ4 – Power Jack




Pin #	Signal Description
1	DC In
2	DC In
3	GND
4	GND

● PJ5 – Power Input Connector




Pin #	Signal Description
1	GND
2	GND
3	DC In
4	DC In

● **J1, J2, J11, J52, J53, J56 – Internal USB
2.0 Pin Header**



Pin #	Signal Description
1	+5VSB
2	+5VSB
3	Data -
4	Data +
5	GND
6	GND

● **J3 – LCD Inverter Wafer Header**



Pin #	Signal Description
1	+12VS
2	+12VS
3	Backlight Control
4	Backlight Enable
5	GND
6	GND

● **J4 – MB Heater Connector**




Pin #	Signal Description
1	+12VSB
2	GND

● **J5, J6, J7, J8 – Panel Heater Connector**




Pin #	Signal Description
1	+12VSB
2	GND

● **J9 – Internal USB 2.0 Pin Header for PCT Touch**




Pin #	Signal Description
1	+5VSB
2	+5VSB
3	Data -
4	Data +
5	GND
6	GND

● J10 – Internal USB 2.0 Pin Header for Webcam



Pin #	Signal Description
1	+5VSB
2	+5VSB
3	Data -
4	Data +
5	GND
6	GND

● J12 – Resistance Touch Screen Interface



Pin #	Signal Description		
	8-wire	4-wire	5-wire
1	UL(X+)	UL(X+)	UL(X+)
2	UR(Y+)	UR(Y+)	UR(Y+)
3	N/A	N/A	PROBE
4	LR(X-)	LR(X-)	LR(X-)
5	LL(Y-)	LL(Y-)	LL(Y-)
6	X+_DRIVE	N/A	N/A
7	Y+_DRIVE	N/A	N/A
8	X-_DRIVE	N/A	N/A
9	Y-_DRIVE	N/A	N/A

● J13 – LVDS Interface




Pin #	Signal Description	Pin #	Signal Description
39	GND	40	GND
37	Ground	38	GND
35	A_TXD3+	36	B_TXD3+
33	A_TXD3-	34	B_TXD3-
31	GND	32	GND
29	A_CLK+	30	B_CLK+
27	A_CLK-	28	B_CLK-
25	GND	26	GND
23	A_TXD2+	24	B_TXD2+
21	A_TXD2-	22	B_TXD2-
19	GND	20	GND
17	A_TXD1+	18	B_TXD1+
15	A_TXD1-	16	B_TXD1-
13	GND	14	GND
11	A_TXD0+	12	B_TXD0+
9	A_TXD0-	10	B_TXD0-
7	GND	8	GND
5	GND	6	GND
3	+LVDS PWR	4	+LVDS PWR
1	+LVDS PWR	2	+LVDS PWR

● J14 – Panel Temp Sensor Connector



Pin #	Signal Description
1	PANEL_SENSOR
2	GND

● J15 / J22 – DDR3L SO-DIMM Interface



J15→ H5.2/J22→ H9.2


Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol
1.	VREFDQ	69.	DQ27.	137.	DQ84.	2.	VSS.	70.	DQ31.	138.	VSS.
3.	VSS.	71.	VSS.	139.	VSS.	4.	DQ4.	72.	VSS.	140.	DQ38.
5.	DQ0.	73.	CKE0.	141.	DQ34.	6.	DQ5.	74.	NC.	142.	DQ39.
7.	DQ1.	75.	VDD.	143.	DQ35.	8.	VSS.	76.	VDD.	144.	VSS.
9.	VSS.	77.	NC.	145.	VSS.	10.	DQS0#.	78.	NC.	146.	DQ44.
11.	DM0.	79.	BA2.	147.	DQ40.	12.	DQS0.	80.	NF/A14.	148.	DQ45.
13.	VSS.	81.	VDD.	149.	DQ41.	14.	VSS.	82.	VDD.	150.	VSS.
15.	DQ2.	83.	A12.	151.	VSS.	16.	DQ6.	84.	A11.	152.	DQS5#.
17.	DQ3.	85.	A9.	153.	DM5.	18.	DQ7.	86.	A7.	154.	DQS5.
19.	VSS.	87.	VDD.	155.	VSS.	20.	VSS.	88.	VDD.	156.	VSS.
21.	DQ8.	89.	A8.	157.	DQ42.	22.	DQ12.	90.	A6.	158.	DQ46.
23.	DQ9.	91.	A5.	159.	DQ43.	24.	DQ13.	92.	A4.	160.	DQ47.
25.	VSS.	93.	VDD.	161.	VSS.	26.	VSS.	94.	VDD.	162.	VSS.
27.	DQS1#.	95.	A3.	163.	DQ48.	28.	DMI.	96.	A2.	164.	DQ52.
29.	DQS1.	97.	A1.	165.	DQ49.	30.	RESET#.	98.	A0.	166.	DQ53.
31.	VSS.	99.	VDD.	167.	VSS.	32.	VSS.	100.	VDD.	168.	VSS.
33.	DQ10.	101.	CK0.	169.	DQS6#.	34.	DQ14.	102.	CK1.	170.	DM6.
35.	DQ11.	103.	CK0#.	171.	DQS6.	36.	DQ15.	104.	CK1#.	172.	VSS.
37.	VSS.	105.	VDD.	173.	VSS.	38.	VSS.	106.	VDD.	174.	DQ54.
39.	DQ16.	107.	A10.	175.	DQ50.	40.	DQ20.	108.	BA1.	176.	DQ55.
41.	DQ17.	109.	BA0.	177.	DQ51.	42.	DQ21.	110.	RAS#.	178.	VSS.
43.	VSS.	111.	VDD.	179.	VSS.	44.	VSS.	112.	VDD.	180.	DQ60.
45.	DQS2#.	113.	WE#.	181.	DQ56.	46.	DM2.	114.	S0#.	182.	DQ61.
47.	DQS2.	115.	CAS#.	183.	DQ57.	48.	VSS.	116.	ODT0.	184.	VSS.
49.	VSS.	117.	VDD.	185.	VSS.	50.	DQ22.	118.	VDD.	186.	DQS7#.
51.	DQ18.	119.	A13.	187.	DM7.	52.	DQ23.	120.	NC.	188.	DQS7.
53.	DQ19.	121.	NC.	189.	VSS.	54.	VSS.	122.	NC.	190.	VSS.
55.	VSS.	123.	VDD.	191.	DQ58.	56.	DQ28.	124.	VDD.	192.	DQ62.
57.	DQ24.	125.	NC.	193.	DQ59.	58.	DQ29.	126.	VREFCA.	194.	DQ63.
59.	DQ25.	127.	VSS.	195.	VSS.	60.	VSS.	128.	VSS.	196.	VSS.
61.	VSS.	129.	DQ32.	197.	SA0.	62.	DQ3#.	130.	DQ36.	198.	EVENT#.
63.	DM3.	131.	DQ33.	199.	VDDSP D.	64.	DQ3.	132.	DQ37.	200.	SDA.
65.	VSS.	133.	VSS.	201.	SA1.	66.	VSS.	134.	VSS.	202.	SCL.
67.	DQ26.	135.	DQS4#.	203.	VTT.	68.	DQ30.	136.	DM4.	204.	VTT.

● **J16 – DICOM Connect**




Pin #	Signal Description
1	ASIC_RST#
2	+3.3VS
3	+3.3VS
4	CSC_DET#
5	SCK_OUT
6	SDA_OUT
7	GND
8	SPI_PROG
9	SPI_CLK
10	SPI_DO
11	SPI_DI
12	SPI_CS

● J17 – Half Mini PCI Express Socket




Pin #	Signal Description	Pin #	Signal Description
1	WAKE#	2	+3.3VSB
3	Reserved	4	GND
5	Reserved	6	+1.5VS
7	CLKREQ#	8	Reserved
9	GND	10	Reserved
11	REFCLK-	12	Reserved
13	REFCLK+	14	Reserved
15	GND	16	Reserved
17	Reserved	18	GND
19	Reserved	20	Reserved
21	GND	22	PERST#
23	PERn0	24	+3.3VSB
25	PERp0	26	GND
27	GND	28	+1.5VS
29	GND	30	SMB_CLK
31	PETn0	32	SMB_DATA
33	PETp0	34	GND
35	GND	36	USB_D-
37	GND	38	USB_D+
39	+3.3VSB	40	GND
41	+3.3VSB	42	Reserved
43	GND	44	Reserved
45	CL_CLK	46	Reserved
47	CL_DATA	48	+1.5VS
49	Controller Link RST#	50	GND
51	Reserved	52	+3.3VSB

● **J18 – 80 Port**




Pin #	Signal Description	Pin #	Signal Description
1	LPC_AD0	2	+5VS
3	LPC_AD1	4	+3.3VS
5	LPC_AD2	6	L80HLAT
7	LPC_AD3	8	L80LLAT
9	GND	10	GND

● **J19 –TPM / ID-394**




Pin #	Signal Description	Pin #	Signal Description
16	+3.3VSB	15	SUS_STAT#
14	SMB DATA	13	GND
12	SMB CLK	11	Debug CLK
10	CLKRUN#	9	LPC Frame#
8	+5VSB	7	LPC AD3
6	+3.3VS	5	LPC AD2
4	SERIRQ	3	LPC AD1
2	PLT reset#	1	LPC AD0

● **J20 – WRDM Pin Header**



Pin #	Signal Description
6	+3.3V_ALWAYS
5	+5V_ALWAYS
4	SOUT
3	GND
2	SIN
1	GND

● **J21 – Battery Socket**




● **J23 – EC Reset connector**



Pin #	Signal Description
1	WRST#
2	GND

● J24 – GPIO Connect



Pin #	Signal Description	Pin #	Signal Description
2	GEN_GPI1	1	GEN_GPO1
4	GEN_GPI2	3	GEN_GPO2
6	GEN_GPI3	5	GEN_GPO3
8	GEN_GPI4	7	GEN_GPO4
10	+5V	9	+5V
12	GND	11	GND

● J25–PCIE X4 Slot for ISO Interface




Pin #	Side B	Side A	Pin #	Side B	Side A
1	+5VSB	+3.3VSB	17	Ground	USBPN
2	+5VSB	+3.3VSB	18	LPC_UART24M	Ground
3	+5VSB	+3.3VSB	19	Ground	Ground
4	+5VSB	+3.3VSB	20	Ground	Ground
5	+5VSB	+3.3VSB	21	Ground	Ground
6	+5VSB	+3.3VSB	22	Ground	Ground
7	Ground	Ground	23	PCIE_RXN	Ground
8	LPC_AD0	+5VS	24	PCIE_RXP	ISOCOM_GPO2
9	LPC_AD1	+5VS	25	Ground	ISOCOM_GPO3
10	LPC_AD2	+3.3VS	26	Ground	PCIE1_CLKRQ#
11	LPC_AD3	ISOCOM_GPO1	27	PCIE_TXN	Ground
12	LPC_FRAME#	USB_PWREN	28	PCIE_TXP	Ground
13	PLT_RST#	Ground	29	Ground	PCIE1_CLKN
14	SERIRQ	Ground	30	PCIE_WAKE#	PCIE1_CLKP
15	Ground	Ground	31	Ground	Ground
16	UARTCLK_24M	USBPP	32	Ground	Ground

● J26 – BIOS Socket




Pin #	Signal Description	Pin #	Signal Description
1	CS0#	5	MOSI
2	MISO	6	SCLK
3	WP	7	HOLD
4	GND	8	+3.3VS

● J27 – For JTAG




Pin #	Signal Description	Pin #	Signal Description
10	Reserved	9	GND
8	Reserved	7	+3.3V
6	Reserved	5	+3.3V
4	C2D	3	GND
2	GND	1	+3.3V

● J28 – Full Mini PCI Express / mSATA Socket




Pin #	Signal Description	Pin #	Signal Description
1	WAKE#	2	+3.3VSB
3	Reserved	4	GND
5	Reserved	6	+1.5VS
7	CLKREQ#	8	Reserved
9	GND	10	Reserved
11	REFCLK-	12	Reserved
13	REFCLK+	14	Reserved
15	GND	16	Reserved
17	Reserved	18	GND
19	Reserved	20	Reserved
21	GND	22	PERST#
23	PERn0	24	+3.3VSB
25	PERp0	26	GND
27	GND	28	+1.5VS
29	GND	30	SMB_CLK
31	PETn0	32	SMB_DATA
33	PETp0	34	GND
35	GND	36	USB_D-
37	GND	38	USB_D+
39	+3.3VSB	40	GND
41	+3.3VSB	42	Reserved
43	MSATA_SEL1	44	Reserved
45	CL_CLK	46	Reserved
47	CL_DATA	48	+1.5VS
49	Controller Link RST#	50	GND
51	MSATA_SEL2	52	+3.3VSB

● **J30 – Standard SATA / SATA DOM Interface**



Pin #	Signal Description
1	Ground
2	Tx+
3	Tx-
4	Ground
5	Rx-
6	Rx+
7	Ground / +5VS

● **J31 – PS2 KB/MS**




Pin #	Signal Description
1	KBDATA
2	MSDATA
3	Ground
4	+5VSB
5	KBCLK
6	MSCLK

● J32 – Cap hotkey Connect



Pin #	Signal Description
1	+5VSB
2	+3.3VSB
3	KP_SCL
4	KP_SDA
5	PWR_LED#
6	KP_P_LED
7	SATA_LED#
8	GND
9	GND

● J33 – Standard SATA Interface




Pin #	Signal Description
1	Ground
2	Tx+
3	Tx-
4	Ground
5	Rx-
6	Rx+
7	Ground

● J34–PCIE X4 Slot Interface




Pin #	Side B	Side A	Pin #	Side B	Side A
1	+12VS	RSVD	17	RSVD	RXN0
2	+12VS	+12VS	18	GND	GND
3	RSVD	+12VS	19	TXP1	RSVD
4	GND	GND	20	TXN1	GND
5	SMBCLK	RSVD	21	GND	RX1
6	SMBDATA	RSVD	22	GND	RX1
7	GND	RSVD	23	TXP2	GND
8	+3.3VS_PCIE	RSVD	24	TXN2	GND
9	RSVD	+3.3VS_PCIE	25	GND	RX2
10	+3.3VSB	+3.3VS_PCIE	26	GND	RX2
11	PCIE_WAKE#	PLT_RST#	27	TXP3	GND
12	PCIE_CLKRQ#	GND	28	TXN3	GND
13	GND	CLKP	29	GND	RX3
14	TXP0	CLKN	30	RSVD	RX3
15	TXN0	GND	31	RSVD	GND
16	GND	RXP0	32	GND	RSVD

● J35 / J36 – Co-lay CPU FAN




Pin #	Signal Description
1	PWM
2	RPM
3	+12VS
4	GND

● J37 – Internal COM4 TTL Serial Port




Pin #	Signal Description	Pin #	Signal Description
2	TTL_DSR#	1	TTL_DCD#
4	TTL_RTS#	3	TTL_SIN
6	TTL_CTS#	5	TTL_SOUT
8	TTL_RI#	7	TTL_DTR#
10	+5VS/+12VS	9	GND

● J38 – System FAN




Pin #	Signal Description
1	PWM
2	RPM
3	+12VS
4	GND

● **J39 – Internal COM5 Serial Port**




Pin #	Signal Description	Pin #	Signal Description
2	232_DSR#	1	232_DCD#
4	232_RTS#	3	232_SIN
6	232_CTS#	5	232_SOUT
8	232_RI#	7	232_DTR#
10	+5VS	9	GND

● **J40 – Internal COM4 Serial Port**




Pin #	Signal Description	Pin #	Signal Description
2	232_DSR#	1	232_DCD#
4	232_RTS#	3	232_SIN
6	232_CTS#	5	232_SOUT
8	232_RI#	7	232_DTR#
10	+5VS	9	GND

● J41 – Internal COM3 Serial Port



Pin #	Signal Description	Pin #	Signal Description
2	232_DSR#	1	232_DCD#
4	232_RTS#	3	232_SIN
6	232_CTS#	5	232_SOUT
8	232_RI#	7	232_DTR#
10	+5VS/+12VS	9	GND

● J42 – Power / HDD LED




Pin #	Signal Description
4	PWR_LED#
3	+3.3VSB
2	+3.3VSB
1	SATA_LED#

● J43 – Internal MIC Connect




Pin #	Signal Description
1	MIC_R
2	MIC_L

● J44 – Internal COM6 Serial Port



Pin #	Signal Description	Pin #	Signal Description
2	232_DSR#	1	232_DCD#
4	232_RTS#	3	232_SIN
6	232_CTS#	5	232_SOUT
8	232_RI#	7	232_DTR#
10	+5VS/+12VS	9	GND

● J45 / J46 –External RJ45 Ethernet Port




Activity/Link LED

Status	Description
OFF	No Link
Blinking	Data Activity
ON	Link

Speed LED


Status	Description
OFF	10 Mbps
Green	100 Mbps
Orange	1 Gbps

● J47,J48 – DisplayPort Interface



Pin #	Signal Description	Pin #	Signal Description
1	ML_LANE0+	11	GND
2	GND	12	ML_LANE3-
3	ML_LANE0-	13	CONFI G1
4	ML_LANE1+	14	CONFI G2
5	GND	15	AUX_CH+
6	ML_LANE1-	16	GND
7	ML_LANE2+	17	AUX_CH-
8	GND	18	HOT PLUG
9	ML_LANE2-	19	RETURN
10	ML_LANE3+	20	+3.3VS

● J49 – Light Sensor Connect




Pin #	Signal Description
1	+3.3V
2	NC
3	Ground
4	SMBCLK
5	LIG_SEN_INT#
6	SMBDATA

● J50, J51 – RIGHT / LEFT CH for Speaker.




Pin #	Signal Description	
	J50 (RIGHT CH)	J51 (LEFT CH)
1	ROUT+	LOUT+
2	ROUT-	LOUT-

● J54 – Heater Error / Heating LEDs




Pin #	Signal Description
3	+3.3V_ALWAYS
2	HEATER_LED#
1	ERROR_LED#

● J55 – Internal COM2 Serial Port




Pin #	Signal Description	Pin #	Signal Description
2	232_DSR#	1	232_DCD#
4	232_RTS#	3	232_SIN
6	232_CTS#	5	232_SOUT
8	232_RI#	7	232_DTR#
10	+5VS/+12VS	9	GND

● J56 – Internal COM1 Serial Port



Pin #	Signal Description	Pin #	Signal Description
2	232_DSR#	1	232_DCD#
4	232_RTS#	3	232_SIN
6	232_CTS#	5	232_SOUT
8	232_RI#	7	232_DTR#
10	+5VS/+12VS	9	GND

● J57 – USB2.0 Port




Pin #	Signal Description	Pin #	Signal Description
1	+5VSB	5	+5VSB
2	Data1-	6	Data2-
3	Data1+	7	Data2+
4	GND	8	GND

● **J58 – Power Switch connect**



Pin #	Signal Description
1	Power ON
2	GND

● **J59 – USB3.0 Port**



Pin #	Signal Description	Pin #	Signal Description
1	+5V	10	+5V
2	Data1-	11	Data2-
3	Data1+	12	Data2+
4	GND	13	GND
5	SSRX1-	14	SSRX2-
6	SSRX1+	15	SSRX2+
7	GND	16	GND
8	SSTX1-	17	SSTX2-
9	SSTX1+	18	SSTX2+

● J60 – Reset Connector



Pin #	Signal Description
1	SYS_RESET#
2	GND

● J61 – Reset Button




Pin #	Signal Description
1	SYS_RESET#
2	GND
3	GND
4	GND

● J62 / J63 – External Audio Phone Jack




Audio Jack	Signal Description
J62	Line Out (stereo) Green
J63	Microphone (stereo) Pink

● J64 – External COM1 Connector



Pin #	Signal Description		
	RS-232	RS-422	RS-485
1	DCD	TX D-	DATA-
2	RXD	TX D+	DATA+
3	TXD	RX D+	--
4	DTR	RX D-	--
5	GND	--	--
6	DSR	--	--
7	RTS	--	--
8	CTS	--	--
9	RI#	--	--

● J65 – External COM2 Connector



Pin #	Signal Description	Pin #	Signal Description
1	DCD	2	RXD
3	TXD	4	DTR
5	GND	6	DSR
7	RTS	8	CTS
9	RI#	10	--




J66,J67– reading light



Pin #	Signal Description
1	+12VSB
2	READING LIGHT



J68– Mechanical hotkey




Pin #	Signal Description
1	PWRSW#
2	Ground
3	Sound up
4	Sound down
5	Ground
6	Brightness up
7	Brightness down
8	+3.3VSB
9	PWRLED#

B. Wake UP on LAN Function

Please make sure the AC power is ON before use the function.

1. Boot into OS (windows XP).
2. In start menu control panel System device manager Network adapters double click Marvell Yukon 88E8071 Advance Wake from Shutdown Item select Wake on Magic packet from power off state.



Please shutdown system and wait for wake on LAN after finish these procedures.